DECLARATION OF PERFORMANCE		No. PIRO/08-2018-09-10	Date: 12/05/2023	
1 Unique product identification code:		PIRO COLLAR PC		
Intended use:	for fire stopping and fire-proof sealing of plastic pipe penetrations through walls or floors.			
Rigid walls with a width f	from 100 mm (aerated co	oncrete, brick, reinforced cor	ncrete)	
Manufacturer: Pirosystem Sp. z o.o. ul. Ogrodnicza 3A, 83-021 Wiślina, POLAND				
Authorised Representative: Pirosystem Sp. z o.o. ul. Ogrodnicza 3A, 83-021 Wiślina, POLAND				
Assessment and verificat	tion of constancy of perfo	ormance	SYSTEM 1	
6a Harmonised standard Specified in point 2 and point 7				
European Assessment Documents	ETA-17/1063	of 06.04.2023	Notified Body Number 1488	
Declared performance, f	ire safety			
Reaction to fire class		B-s2,d0		
Fire resistance		from El 120 or El 180		
Declared performance hygiene, health, environment				
The Applicant submitted a written statement that the product and/or its ingredients do not contain substances classified as hazardous according to EOTA TR 034*				
Durability			72	
Release of hazardous sul outdoor use.	ostances (declaration) (*)	. Hygienic Certificate: the pro	oduct is intended for indoor or	
8 Technical documentation: Technical Data Sheet, Pirosystem Sp. z o.o. Product Catalogue				
	Unique product identifice Intended use: Rigid floors with a width Rigid walls with a width Manufacturer: Authorised Representati Assessment and verificate Harmonised standard Span European Assessment Documents Declared performance, for Reaction to fire class Fire resistance Declared performance has The Applicant submitted substances classified as I Durability Release of hazardous sull outdoor use.	Unique product identification code: Intended use: Rigid floors with a width from 150 mm (reinforced Rigid walls with a width from 100 mm (aerated conflexible walls with a width of 125 mm or more (plexible walls	Unique product identification code: Intended use: For fire stopping and fire-proof sealing of plastic pipe floors. Rigid floors with a width from 150 mm (reinforced concrete) Rigid walls with a width from 100 mm (aerated concrete, brick, reinforced corflexible walls with a width of 125 mm or more (plasterboard, wood) Manufacturer: Pirosystem Sp. z o.o. ul. Ogrodnicza 3A, 83-C Authorised Representative: Pirosystem Sp. z o.o. ul. Ogrodnicza 3A, 83-C Assessment and verification of constancy of performance Harmonised standard Specified in point 2 and point 7 European Assessment Documents ETA-17/1063 Declared performance, fire safety Reaction to fire class Fire resistance Declared performance hygiene, health, environment The Applicant submitted a written statement that the product and/or its ingresubstances classified as hazardous according to EOTA TR 034* Durability Release of hazardous substances (declaration) (*). Hygienic Certificate: the product or use.	

The performance of the described afore product corresponds to the declared performance. This declaration of performance has been issued in accordance with Regulation (EU) No. 305/2011 under the sole responsibility of the said manufacturer.

Place, date of issue	Wiślina, 2023-05-12	
On behalf of the manufacturer, signed by	President of the Management Board Marcin Gierej	
	Pirosystem sp. z o.o. ul. Ogrodnicza 3A 83-021 Wiślina nip 6040200582 regon 369982224	