

		FLEXIBLE WALL EI 120 width 100 mm			RIGID WALL EI 120 width 150 mm			FLOOR EI 120 width 150 mm		
		Plastic pipe wall thickness selected from ETA			Plastic pipe wall thickness selected from ETA			Plastic pipe wall thickness selected from ETA		
Pipe diameter	Selected collar	PVC	PE-HD, PE, ABS, SAN+ PVC	PP	PVC	PE-HD, PE, ABS, SAN+ PVC	PP	PVC	PE-HD, PE, ABS, SAN+ PVC	PP
mm	PC SLIM	mm	mm	mm	mm	mm	mm	mm	mm	mm
55	PC-55-30	2,1	1,8	2,0	2,7	6,6	2,4	3,4	7	7,2
68	PC-68-30	2,4	1,9	2,1	3,3	6,6	3	3,4	7	7,3
75	PC-82-30	2,7	1,9	2,3	3,6	6,6	3,4	3,4	7	7,4
82	PC-90-30	2,9	2,0	2,4	3,7	6,6	3,6	3,4	7	7,5
90	PC-110-30	3,3	2,0	2,6	4,6	6,6	4,4	3,4	7	7,6
110	PC-125-30	3,6	2,1	2,8	5,2	8,3	4,8	6	10	8
125	PC-135-30	3,9	2,1	2,9	5,6	8,3	5	6,5	10	8,1
160	PC-160-30	4,4	2,2	3,2	6,4	9,5	6,2	6,5	10	6,8

CAUTION:

Plastic pipe wall thickness may vary depending on the material and purpose of the pipe. In accordance with the standards for PVC, PP, PEHD pipes (PN-EN 1451-1_2001P, PN-EN 1555-2_2012P, PNEN-1401-1_2009P) standard point 6.2.5 Wall thickness - the wall thickness may vary in relation to the nominal , and the maximum tolerance is variable and depends on the diameter of the pipe and can be from 0,3 to 1mm.