

	<b>DECLARATION OF PERFORMANCE</b>		<b>No.</b> <b>PIRO-04-2017-12-31</b>	<b>Date: 15/11/2019</b>
1	Unique product identification code		<b>PIRO ACRYLIC SEALANT AC 120</b>	
2	Intended use:	for fire stopping and fire-proof sealing of linear joints or gaps in walls and ceilings		
2a	Rigid ceilings with a width from 150 mm (reinforced concrete) Rigid walls with a width from 150 mm (aerated concrete, brick, reinforced concrete) Linear joints with a width up to 100 mm (auxiliary material: mineral wool or foam)			
3	Manufacturer:	Pirosystem Sp. z o.o. ul. Ogrodnicza 3A, 83-021 Wiślina, Poland		
4	Authorised Representative:	Pirosystem Sp. z o.o. ul. Ogrodnicza 3A, 83-021 Wiślina, Poland		
5	Assessment and verification of constancy of performance			<b>SYSTEM 1</b>
6a	Harmonised standard Specified in point 2 and point 7 .....			
6b	European Assessment Documents	ETA-17/1059	of 14/12/2017	Notified Body Number 1488
7	Declared performance, fire safety			
	Reaction to fire class		B-s2,d0	
	Fire resistance		up to EI 120	
	Declared performance hygiene, health, environment			
	Hygienic Certificate		BK/B/0264/01/2019	
	Durability and fitness for use		Not specified	
	Release of hazardous substances (declaration) (*) Hygienic Certificate: products for indoor and outdoor use.			
8	Technical documentation: Technical Data Sheet, Pirosystem Polska Sp. z o.o. Product Catalogue			
<b>The performance of the described afore product corresponds to the declared performance. This declaration of performance is issued at sole responsibility of the aforesaid producer, in accordance with EU Regulation no. 305/2011</b>				
Place, date of issue			Wiślina, 02/01/2020	
On behalf of the manufacturer, signed by			President of the Management Board Marcin Gierej	